

CL-W6045

Ruban de toile a masquer pour les applications de stuc en une étape

Le produit CL-W6045 est un ruban adhésif de toile de 9,5 mils doté d'un support de polyéthylène à lamination spéciale visant à prévenir la pénétration des rayons UV.

Applications

- Surface adhésive laissant peu de résidus
- Bonne résistance aux intempéries, le rendant idéal pour des travaux de masquage dans le domaine de la construction et pour brider des tuyaux en acier à l'extérieur

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

Épaisseur	9,5 mils
Support	Toile laminée de polyéthylène
Résistance à la rupture	25,0 lb/po
Adhésif	Caoutchouc
Capacité adhésive	22,0 oz/po

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the

legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.