

OV-G5209

Pellicule de surlamination de polypropylène à fini mat

Le produit OV-G5209, d'une épaisseur de 1,5 mil, est une pellicule de surlamination de PPBO, translucide, autoenroulée, dotée d'un adhésif acrylique à base d'eau. Il offre une excellente résistance aux acides, aux produits chimiques et à l'huile.

Applications

- Renforcement, protection de surfaces et scellage de rubans
- Embellissement, protection et prolongation de la durée d'étiquettes imprimées

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

Épaisseur	1,5 mil
Support	PPBO à fini mat
Résistance à la rupture	13 oz/po
Adhésif	Acrylique à base d'eau
Capacité adhésive à l'acier	13 - 16 oz/po
Allongement à la rupture	190%
Approbation FDA	21 CFR 175.105 / 21 CFR 177.1520

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise,

determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.