

# RE-K6728

## Ruban répulpable simple face

RE-K6728 est un ruban adhésif répulpable à un seul revêtement de 6,5 mils avec un support de papier extensible et revêtu d'un adhésif acrylique modifié soluble dans l'eau.

### Applications

- Recommandé pour l'onglet ou les épissures temporaires ou permanentes sur le papier de poids lourd, revêtu et non revêtu.

### Caractéristiques

- Très haute résistance à la traction
- Haute résistance à la chaleur et adhérence
- Répond au TAPPI 213 Norme répulpable

### Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

Épaisseur	6,5 mils
Support	Papier kraft
Résistance à la rupture	28,5 lb/po
Capacité adhésive	≥ 35 oz/po
Allongement à la rupture	5%
Température de service	200°C - 392°F
Couleur	Blanc, Bleu, Kraft

reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOTape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOTape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOTape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.