

DC-U101A

High Tack Double Sided UPVC Tape

DC-U101A a double sided UPVC tape incorporating an exceptionally high tack, high peel, acrylic adhesive system. DC-U101A performs well in many difficult bonding and splicing applications. Recommended application temperature to achieve best results is 65°F (18°C).

Application

- Product assembly
- Difficult bonding and splicing applications
- Lamination to EPDM rubber, plastics, glass, and urethane foams

Features & Benefits

- Exceptionally high tack and peel
- UPVC film allows conformability
- High adhesive mass provides excellent gap filling properties
- Excellent resistance to environmental extremes
- Exhibits excellent adhesion to ether and ester foams
- Bonds well to rough or porous surfaces
- Excellent water resistance

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a



surface that is clean, dry and free of grease, oil or other contaminants.

Sizes

- 6mm x 55m
- 9mm x 55m
- 12mm x 55m
- 18mm x 55m
- 24mm x 55m
- 36mm x 55m
- 48mm x 55m
- 72mm x 55m
- custom slitting

Technical Data

| | |
|---------------------|--------------------------------|
| Carrier | 1.5 mils UPVC |
| Adhesive | Acrylic |
| Release Liner | 60# Kraft |
| Total Thickness | 8.5 mils |
| Adhesion | 136 oz/in |
| Service Temperature | -20°F to 200°F (-29°C to 93°C) |
| Elongation | 60% |
| Color | Transparent |

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise,



determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.