

## **FS-G7736**

### **All Weather Lamtec WMP®-50 Facing Tape**

FS-G7736 is an adhesive tape used primarily to seal and seam Lamtec® WMP-50 faced Insulation used in metal buildings. It is coated with a high performance cold weather acrylic adhesive offering a superior quick stick, it also provides a strong bond and great performance at low temperatures. The paper release liner protects the adhesive from contaminants when you need to cut the tape to specific lengths for use in tight areas ensuring a strong bond once applied.

Lamtec and WMP are registered trademarks of Lamtec Corporation.

#### **Application**

- Use to seam and join Lamtec® WMP-50 faced insulation
- Use to repair tears on Lamtec® WMP-50 faced insulation

#### **Features & Benefits**

- An initial quick stick helps speed up application
- Creates a strong bond
- Easy to remove paper liner
- Excellent vapor barrier & low WVTR (Water Vapor Transmission Rate)
- Outstanding performance across a broad range of temperatures
- Excellent low temperature bonding

#### **Storage & Usage Conditions**

Store tape in its original packaging away from direct



sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

## Sizes

2.83 in x 50 yd | 72 mm x 45,72 m

## Technical Data

Carrier	Poly film/Scrim/Kraft
Adhesive	Acrylic
Release Liner	Siliconized Paper
Total Thickness	8.5 mils
Tensile	42 lbs/in
Adhesion	40.0 oz/in
Application Temperature	-4°F to 104°F (-20°C to 48°C)
Service Temperature	-40°F to 176°F (-40°C to 80°C)
Elongation	1%
Color	White

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be



liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.