

Polyethylene Block Out Tape

PR-N3201 is a polyethylene block out tape that's used for screen printing. You can apply this durable (5 mils) tape to both sides of the screen. The polyethylene tape forms an aggressive bond that resists inks and cleaning solvents and can withstand multiple washings. You'll love the clean removal of the tape in one piece – from wood frames and screens – with no adhesive residue left behind. This conformable, self-wound block out tape is all weather and UV resistant for up to 30 days.

APPLICATIONS FOR THE TAPE

The most common applications for the polyethylene tape include:

- screen printing (as a block out tape to prevent ink and cleaning solutions from creeping between the screen and the frame)
- general masking (where high adhesion is required)

FEATURES OF THE TAPE

Features of the polyethylene block out tape include:

- durable
- solvent resistant
- moisture resistant
- aggressive adhesive won't damage screens
- tape remains intact through multiple cleaning/washing

cycles

- clean removal
- conformable in frame corners

TAPE ADHESIVE

The tape has a solvent acrylic.

WEATHER RESISTANCE

The polyethylene block out tape is weather resistant:

- all weather tape
- moisture resistant
- UV resistant for 30 days

TAPE COLORS

The polyethylene tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- screen printers
- print shops

ECHOtape PART NUMBER

The part number for this tape is PR-N3201.

Application

- General purpose screen block out tape to prevent ink from creeping between screen and frame



- General masking where high adhesion is required

Features & Benefits

- Solvent and moisture resistant
- Remains in tact during cleaning cycle
- Conformable in frame corners
- Aggressive adhesive will not damage screen
- Clean removal

Technical Data

SIZES	1" x 6" x 108' custom slitting
CARRIER	Polyethylene
ADHESIVE	Solvent Acrylic
TOTAL THICKNESS	5 mils
TENSILE	10 lbs/in
ADHESION	24 oz/in
ELONGATION	150%
COLOR	Blue, White

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape



works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.