

## **PR-N3287**

# **Self Adhesive Protective Film for Windows**

PR-N3287 is a reliable self-adhesive protective window film offering temporary protection during outdoor stucco applications. PR-N3287 is ideal for stucco contractors, builders, remodellers, painters and masons as a temporary protection film that protects against stucco and paint overspray as well as mortar.

## **Application**

- Masking windows in construction projects (i.e. stucco and masonry)

## **Features & Benefits**

- Easy to unwind and apply by hand
- Easy to remove
- Removes cleanly without leaving adhesive residue
- UV resistant for 180 days in all weather

## **Storage & Usage Conditions**

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.



## Sizes

24" x 600'

## Technical Data

|                                |                               |
|--------------------------------|-------------------------------|
| Carrier                        | Low Density Polyethylene Film |
| Adhesive                       | Acrylic                       |
| Total Thickness                | 2 mils                        |
| Tensile                        | 5.5 lbs/in                    |
| Adhesion                       | 2 oz/in                       |
| Maximum Temperature Resistance | 140°F (60°C)                  |
| Elongation                     | Long. >300% / Trans. >500%    |
| UV Resistance                  | 180 days                      |
| Color                          | Blue, Transparent             |

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage if its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.