

Single Sided Repulpable Tabbing Tape

RE-K7333 is a single-sided, repulpable adhesive tape (3.5 mils) that works well on uncoated and coated lightweight paper. The repulpable tape is coated with a water soluble, modified acrylic adhesive. The tape meets the TAPPI 213 repulpable standard and has high adhesion, high heat resistance, and very high tensile strength.

APPLICATIONS FOR THE TAPE

The most common applications for the single-sided, repulpable tape include:

- tabbing lightweight uncoated and coated paper
- temporary or permanent butt slices of lightweight uncoated and coated paper

FEATURES OF THE TAPE

Features of the single-sided, repulpable tape include:

- very high tensile strength
- high adhesion
- high heat resistance
- repulpable
- meets the TAPPI 213 repulpable standard

TAPE ADHESIVE

The tape has a water soluble, modified acrylic adhesive.



TAPE COLORS

The single-sided, repulpable tape is available in white.

WHO USES THE TAPE

The tape is most commonly used by:

- paper manufacturers
- printers
- publishers
- manufacturers

ECHOtape PART NUMBER

The part number for this tape is RE-K7333.

Application

- Recommended for tabbing or the temporary or permanent butt splices of light weight, uncoated and coated paper

Features & Benefits

- Very high tensile strength
- High heat resistance and adhesion
- Meets TAPPI 213 repulpable standard°

Technical Data

SIZES	Please call for sizes and availability
-------	--

CARRIER	White Siliconized Repulpable Paper
ADHESIVE	Water Soluble Acrylic
TOTAL THICKNESS	3.5 mils
TENSILE	28.5 lbs/in
ADHESION	35 oz/in
MAXIMUM OPERATING TEMPERATURE	392°F (200°C)
ELONGATION	5%
COLOR	White, Blue

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes



no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.