

# Double Sided Repulpable Tape For Flying Splices

RE-T6702 is a double-sided, repulpable adhesive tape that's used for flying splices. The repulpable tape has a silicone coated glassine paper liner and is coated with a water soluble, acrylic adhesive. The tape has a very high wet grab.

## APPLICATIONS FOR THE TAPE

The most common applications for the double-sided, repulpable tape include:

- high-speed automatic splicing on newsprint offset printing
- high-speed automatic splicing on web printing
- high-speed automatic splicing on flexographic printing
- high-speed automatic splicing on rotogravure printing

## FEATURES OF THE TAPE

Features of the double-sided, repulpable tape include:

- very high wet grab
- repulpable

## TAPE ADHESIVE

The tape has a water soluble, acrylic adhesive.



---

## TAPE SIZES

The double-sided, repulpable tape is available in the following sizes:

- 1/2 inch by 36 yards / 12 mm by 33 m
- 3/4 inch inches by 36 yards / 18 mm by 33 m
- 1 inch by 36 yards / 24 mm by 33 m

## TAPE COLORS

The double-sided repulpable tape is available in light green.

## WHO USES THE TAPE

The tape is most commonly used by:

- newspaper publishers
- printers

## ECHOtape PART NUMBER

The part number for this tape is RE-T6702.

## Application

- Recommended for high speed automatic splicing on newsprint offset, web, flexographic and rotogravure printing.

## Technical Data

SIZES	12 mm x 33 m 18 mm x 33 m 24 mm x 33 m
CARRIER	Non-Woven Paper
ADHESIVE	Light Green, Water Soluble Acrylic
RELEASE LINER	Silicone Coated Glassine Paper
TOTAL THICKNESS	3.94 mil
ADHESION	Wood Free Paper: 50.3 oz/in / Steel Panel: 57.1 oz/in

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

—

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECH0tape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes



---

no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.